





Proliftix[®] Crank

Adjustable Height Tables




*Fits the most popular spaces,
with over 20 sizes available*



*At 5 turns/inch, easily adjust
height from 27 1/4" to 43 1/4"*



*Crank adjustment meets tight
budget requirements*



*Add on Proxi accessories to
keep you organized*

Worksurface Height Adjustment in Reach

With a crank height-adjustable table, standing is as simple as sitting. Just raise the work surface and change your whole perspective!

Crank Adjustment

- Adjusts from 27 1/4" - 43 1/4" at 5 turns per inch with minimal effort.
- Crank handle located above right leg; can be removed and stowed once height is set.

Valued Features


- Flexibility - With over 20 models to choose from and the optional Proxi[®] Rail accessories, configurations are virtually limitless.
- Strength - 225 lb. table base capacity supports the equipment needs of today's computer-intensive work environments.
- Plan for any office configuration – big or small, with a variety of work surface shapes and sizes.
- Create the look and feel in your office with a broad selection of laminates.
- Protection - Your investment is protected with our limited lifetime warranty and a 5 year warranty on the crank mechanism.

Additional Range

For extended reach, select a bi-level worksurface with 22 1/4" - 50 1/4" height range, exceeding ANSI/BIFMA 5th - 95th percentile requirements.

Proliftix Crank – Adjustable Height Tables

Rectangular




- Adjusts from 27 1/4" - 43 1/4" at 5 turns per inch
- Crank handle located above right front leg
- Handle can be removed once height is set
- Two leg table
- 225 lbs. load capacity

Nominal
Dimensions

W	D	Model #	Laminate ¹	Edge	Weight
36	24	TKCB3624	<input type="text"/>	- 02	88
42	24	TKCB4224	<input type="text"/>	- 02	93
48	24	TKCB4824	<input type="text"/>	- 02	99
60	24	TKCB6024	<input type="text"/>	- 02	111
72	24	TKCB7224	<input type="text"/>	- 02	122
36	30	TKCB3630	<input type="text"/>	- 02	88
42	30	TKCB4230	<input type="text"/>	- 02	93
48	30	TKCB4830	<input type="text"/>	- 02	99
60	30	TKCB6030	<input type="text"/>	- 02	111
72	30	TKCB7230	<input type="text"/>	- 02	122


Rectangular - Bi-level



- Adjusts from 27 1/4" - 43 1/4" at 5 turns per inch
- Front surface 12" height range with +/- 15° tilt
- Crank handle located above right front leg
- Handle can be removed once height is set
- Two leg table
- 225 lbs. load capacity

30	36	TKCB3035B	<input type="text"/>	- 02	141
36	36	TKCB3635B	<input type="text"/>	- 02	149
48	36	TKCB4835B	<input type="text"/>	- 02	166


Equal Corner - 2 Legs



- Adjusts from 27 1/4" - 43 1/4" at 5 turns per inch
- Crank handle located above right front leg
- Handle can be removed once height is set
- Two leg table
- 225 lbs. load capacity

W/L	W/R	D	Model #	Laminate ¹	Edge	Weight
42	42	24	TKCB424224	<input type="text"/>	- 02	108
45	45	24	TKCB454524	<input type="text"/>	- 02	113
48	48	24	TKCB484824	<input type="text"/>	- 02	118
48	48	30	TKCB484830	<input type="text"/>	- 02	123

Equal Corner - 2 legs, Bi-level



- Adjusts from 27 1/4" - 43 1/4" at 5 turns per inch
- Front surface 12" height range with +/- 15° tilt
- Crank handle located above right front leg
- Handle can be removed once height is set
- Two leg table
- 225 lbs. load capacity

42	42	24	TKCB424224B	<input type="text"/>	- 02	153
45	45	24	TKCB454524B	<input type="text"/>	- 02	164
48	48	24	TKCB484824B	<input type="text"/>	- 02	164
48	48	30	TKCB484830B	<input type="text"/>	- 02	174

TO ORDER SPECIFY

- 1) Model, width & depth of work surface (eg TKCB4824)
- 2) Laminate (eg SG241)
- 3) Edge Treatment (eg 02)
Example: TKCB4824-SG241-02

Notes:

1. For available laminates and edge treatment, please see Color and Trim Options in the Idea at Work Pricing & Specification Guide.
2. Paint finish is Black only
3. For base-only configurations, only the model # is required (eg TKCB4824)
4. **Note, dimensions provided above are nominal.** Actual widths of all tables are reduced by 2" and depths by 1". For example, a nominal 48" x 24" rectangular table has an actual dimension of 46" x 23".

5. Dual Surface specifications: Front surface adjusted using Brutus (ATK50) arm with +5 7/8", -6 1/2" height range and +/- 15° tilt range. Front surface laminate and trim matches main work surface.
6. Work surfaces are pre-drilled with mounting location for bases and dual surface platform (if any).
7. All tables and bases ship unassembled. Weight information is shipped weight for base only.
8. Moving work surfaces can collide with other components. Installation of overhead storage or wall mounted accessories in the path of the work surface is not recommended.
9. 225 lbs. load capacity is for table base only.
10. To add tool bars and accessories which move with the work surface and can accept a variety of desk accessories, see the Proxi Accessories Cut Sheet.

The following are federally registered trademarks of Workrite Ergonomics: Workrite Ergonomics®, Proliftix®. The following is a trademark of Workrite Ergonomics: Idea at Work™.



Printed with 25% post-consumer waste, 50% total recycled content.
1400107-0408 ©2008 Contents subject to change without notice.

Idea at Work
1450 Technology Lane
Petaluma, CA 94954
www.idea-at-work.com
800.959.9675

